

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

WARTIME REPORT

ORIGINALLY ISSUED

May 1946 as
Restricted Bulletin E6D22

THE KNOCK-LIMITED PERFORMANCE OF FUEL BLENDS CONTAINING
SPIROPENTANE, METHYLENECYCLOBUTANE, DI-tert-BUTYL
ETHER, METHYL tert-BUTYL ETHER, AND TRIPTANE

By Carl L. Meyer

Aircraft Engine Research Laboratory
Cleveland, Ohio

NACA

WASHINGTON

NACA WARTIME REPORTS are reprints of papers originally issued to provide rapid distribution of advance research results to an authorized group requiring them for the war effort. They were previously held under a security status but are now unclassified. Some of these reports were not technically edited. All have been reproduced without change in order to expedite general distribution.

NACA RB No. E6D22

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESTRICTED BULLETIN

THE KNOCK-LIMITED PERFORMANCE OF FUEL BLENDS CONTAINING

SPIROPENTANE, METHYLENECYCLOBUTANE, DI-tert-BUTYLETHER, METHYL tert-BUTYL ETHER, AND TRIPTANE

By Carl L. Meyer

INTRODUCTION

A general investigation is being conducted at the NACA Cleveland laboratory to determine the effectiveness of various compounds as antiknock agents for aviation fuels. As a part of this program, limited quantities of spiropentane, methylenecyclobutane, and di-tert-butyl ether were synthesized for exploratory tests. Methyl tert-butyl ether and triptane, which had been commercially obtained, were used for comparative purposes. Knock-limited tests were made in a 17.6 engine of blends containing each of the five compounds individually blended with S-4 reference fuel to a concentration of 20 percent by volume; the final blends contained 4 ml TEL per gallon. The data were obtained in August 1945.

APPARATUS AND TEST PROCEDURE

A description of the apparatus is given in reference 1. The tests were conducted with a 17.6 engine at the following engine conditions:

Engine speed, rpm	1800
Compression ratio	7.0
Outlet-coolant temperature, °F	212
Inlet-air temperature, °F	250, 100
Spark advance, deg B.T.C.	30

PRESENTATION AND DISCUSSION OF RESULTS

The knock-limited performance at an inlet-air temperature of 250° F of leaded blends containing spiropentane and methylenecyclobutane is presented in figure 1; the knock-limited performance at

inlet-air temperatures of 250° F and 100° F of leaded blends containing di-tert-butyl ether, methyl tert-butyl ether, and triptane is presented in figure 2. All data at a given inlet-air temperature were obtained during a single operating day. The data of figures 1 and 2 are summarized in table I.

The 20-percent addition of spiropentane (fig. 1) decreased the knock-limited power of the base fuel at all fuel-air ratios below 0.085 but permitted gains at richer fuel-air mixtures. Methylene-cyclobutane decreased the knock-limited power of the base fuel at all fuel-air ratios below 0.112. Because of the lack of material, knock-limited performance data were not obtained for the spiropentane blend at fuel-air ratios greater than 0.10; additional tests to determine the effect of a change in inlet-air temperature on the knock-limited performance of either of the two aforementioned blends were not possible for the same reason.

Di-tert-butyl ether, methyl tert-butyl ether, and triptane (fig. 2) increased the knock-limited power of the base fuel at all fuel-air ratios and at both inlet-air temperatures. Methyl tert-butyl ether was the most effective antiknock agent of the three compounds. Di-tert-butyl ether was more effective than triptane at fuel-air ratios below 0.07 at the higher inlet-air temperature and at all fuel-air ratios at the lower inlet-air temperature. (Under other test conditions, reference 2 showed that di-tert-butyl ether had better antiknock qualities than methyl tert-butyl ether at fuel-air ratios below about 0.065.) Blends containing the three compounds are more sensitive at fuel-air ratios of 0.065 and 0.07 to changes in inlet-air temperature (table I(b)) than the base fuel; methyl tert-butyl ether was the most sensitive in the aforementioned fuel-air-ratio range.

Aircraft Engine Research Laboratory,
National Advisory Committee for Aeronautics,
Cleveland, Ohio.

REFERENCES

1. Meyer, Carl L., and Branstetter, J. Robert: The Knock-Limited Performance of Fuel Blends Containing Aromatics. Part I - Toluene, Ethylbenzene, and p-Xylene. NACA ARR No. E4J05, 1944.
2. Alquist, Henry E., and Tower, Leonard K.: Suitability of Ethers as Aviation Fuel Components. The Knock-Limited Performance of Several Ethers Blended with AN-F-28 Fuel. NACA CB No. E5A04, 1945.

TABLE I - SUMMARY OF TEST DATA

[17.6 engine; compression ratio, 7.0; engine speed, 1800 rpm; spark advance, 30° B.T.C.; outlet-coolant temperature, 212° F]

(a) Relative performance

Compound	Blend composition (percent by volume)		Tetraethyl lead (ml/ gal)	imep ratio ^a				
				Fuel-air ratio				
	Compound	S-4		0.065	0.07	0.085	0.10	0.11
Inlet-air temperature, 250° F								
S-4 reference fuel	0	100	4	1.00	1.00	1.00	1.00	1.00
Spiropentane	20	80	4	0.84	0.86	1.00	1.09	----
Methylenecyclobutane				.77	.81	.89	.95	0.99
Di- <u>tert</u> -butyl ether				1.19	1.15	1.14	1.16	1.17
Methyl <u>tert</u> -butyl ether				1.26	1.25	1.37	1.45	1.47
Triptane				1.14	1.15	1.20	1.21	1.19
Inlet-air temperature, 100° F								
S-4 reference fuel	0	100	4	1.00	1.00	1.00	1.00	1.00
Di- <u>tert</u> -butyl ether	20	80	4	1.28	1.26	1.23	1.20	1.19
Methyl <u>tert</u> -butyl ether				1.40	1.42	1.41	1.41	1.40
Triptane				1.19	1.21	1.17	1.15	1.16

$$^a \text{imep ratio} = \frac{\text{imep (20 percent compound + 80 percent S-4 + 4 ml TEL/gal)}}{\text{imep (S-4 + 4 ml TEL/gal)}}$$

(b) Relative temperature sensitivity

Compound	Blend composition (percent by volume)		Tetraethyl lead (ml/ gal)	Relative temperature sensitivity ^a				
				Fuel-air ratio				
	Compound	S-4		0.065	0.07	0.085	0.10	0.11
S-4 reference fuel	0	100	4	1.00	1.00	1.00	1.00	1.00
Di- <u>tert</u> -butyl ether	20	80	4	1.08	1.10	1.08	1.03	1.02
Methyl <u>tert</u> -butyl ether				1.11	1.14	1.03	.97	.95
Triptane				1.04	1.05	.98	.95	.97

^aRelative temperature

$$\text{sensitivity} = \frac{\text{imep ratio (inlet-air temperature, 100° F)}}{\text{imep ratio (inlet-air temperature, 250° F)}}$$

National Advisory Committee
for Aeronautics




Figure 1. - The knock-limited performance of leaded blends containing spiropentane and methylenecyclobutane individually blended with S-4 reference fuel. 17.6 engine; compression ratio, 7.0; engine speed, 1800 rpm; spark advance, 30° B. T. C.; outlet-coolant temperature, 212° F.

Fig. 2

NACA RB No. E6D22




Figure 2. - The knock-limited performance of leaded blends containing di-tert-butyl ether, methyl tert-butyl ether, and triptane individually blended with S-4 reference fuel. 17.6 engine; compression ratio, 7.0; engine speed, 1800 rpm; spark advance, 30° B. T. C.; outlet-coolant temperature, 212° F.

LANGLEY RESEARCH CENTER



3 1176 01364 8341